



LNG

Custody Transfer System



MUSASINO CO., LTD.

☐ Head Office
1-2-15 MinamiYukigaya, Ota-ku, Tokyo, 145-0066
Tel.+81-3-3726-4413 Fax.+81-3-3726-1557
E-mail : sales@musasino.co.jp / service1@musasino.co.jp
<https://www.musasino.biz>

Distributor:

MUSASINO CO., LTD.

LNG Custody Transfer System

As environmental regulations change, and the demand for LNG increases, it is important to have an accurate and reliable custody transfer system on your carriers. Musasino’s CTS is built on our extensive experience in the marine industry, and our unique technologies.

FEATURES

1 Unique Self-Correction Function

The radar type liquid level sensors are equipped with a self-calibration function that ensures accurate measurements over long-term operation.

2 All-in-One Structure


The all-in-one design combines modules for level sensors, temperature sensors, and pressure sensors in a single housing. Each module is independent, and can be maintained without having to open the tank. Musasino’s in-house developed transducer makes it possible to take stable measurements with less attenuation and less interference from any unevenness in the guide pipe.

3 Bottom Structure

Musasino’s unique bottom attenuator has a simple form and requires little space for installation. This allows for measurements down to 15 mm from the tank bottom, and with an accuracy of ± 5 mm down to 25 mm above the tank bottom.

4 Designed for Durability

The inside of an LNG tank is a harsh environment, and the installation has to hold up under those conditions for decades. Simulations using sloshing models show our design is robust enough to withstand over 40 years of operations.



Level Gauge

| | |
|----------------------|--|
| Measuring Method | FMCW (Frequency Modulated Continuous Wave) |
| Measurement Range | 0.5m to 50m |
| Resolution | 1mm |
| Accuracy | ± 5 mm |
| Ambient Temperature | -30 to +70°C (Electronics Housing) |
| Explosion Protection | Intrinsically Safe Type Ex ia IIC T5 |
| Protection Class | IP66 |
| Material | SUS316L |

Inclinometer

| | |
|-------------------|------------------------|
| Method | Capacitive MEMS Sensor |
| Measurement Range | $\pm 5^\circ$ |
| Accuracy | $\pm 0.05^\circ$ |
| Resolution | 0.001° |

Temperature Sensor

| | |
|-------------------|---|
| Method | PT-100, 4-wire Temperature Sensor |
| Measurement Range | -200 to +100°C |
| Accuracy | $\pm 0.2^\circ\text{C}$ ($\leq -145^\circ\text{C}$), $\pm 1.5^\circ\text{C}$ ($> -145^\circ\text{C}$) |
| Resolution | 0.1°C |

Pressure Sensor

| | |
|--------------------|------------------------------------|
| Method | Diaphragm with Strain Gauge Bridge |
| Measurement Range | 0.8 bar to 1.4 bar |
| Accuracy | $\pm 0.5\%$ FS |
| Resolution | 1 mbar |
| Diaphragm Material | SUS 316L |

